



Classic Paver Bond

A WATER BASED SINGLE COMPONENT PAVER PROTECTOR



COVERAGE:

1 Gallon
Pavers (80 to 125 sq. ft.)
Slate (200 to 350 sq. ft.)

PACKAGING:

Available in 1 gallon jugs, 5 gallon pails and 55 gallon drums.

STORAGE:

1. Store in a cool, dry location.
2. Store out of direct sunlight.
3. Protect pails and jugs from weather and other damage.
4. Store at a temperature between 40°F (4°C) and 90°F (32°C).

SHELF LIFE:

2-3 years
Unopened in its original container

Visit us online:
ClassicCoatingsSystems.com

See Our Website Gallery
to Get Inspired and
View How-to Videos & SDS

DESCRIPTION

Classic Paver Bond Wet-Look seals & protects pavers from UV degradation & fading. It is environmentally safe with low voc and cleans up with soap and water. Paver Bond is a single component, state of the art formula that makes it easy to apply. It darkens the pavers with a wet look & medium Sheen. It is designed for a deeper penetration by sealing and interlocking concrete pavers and by stabilizing joint sand that locks it in place. It can enhance color & also be used for porous brick, flagstone, slate & porous concrete. Paver Bond can be resealed years later without stripping by clearing the surface with a pressure washer 2700 PSI. Paver Bond stops sand from being washed away due to regular cleaning and by rain. For interior and exterior use. **CAUTION:** May be slippery when wet. To combat, we highly recommend adding Classic Gator Grip during the second application of Paver Bond with a 9" nap roller from 3/8" to 1/2".

ADVANTAGES

Environmentally friendly with low voc <50g/l
High UV stable and resists water penetration
Color enhancing & sand joint stabilizing
Reseal without stripping. Flexible & dries clear
Non-flammable, no fumes/harmful chemicals
Stops weeds and mildew growth
Easy to apply with a garden type pump sprayer

LIMITATIONS

May reflect working cracks in substrate
May be slippery when wet
Must be installed over a clean and dry surface
Not for use under water and freeze thaw
Application temperature should be between 55°F and 90°F

TYPICAL USAGE

Classic Paver Bond is safe for both indoor and outdoor use which includes the following but not limited to:

- Pavers
- Slate
- Spanish Tile
- Natural Stone
- Porous Brick
- Porous Concrete
- Flagstone



Classic Paver Bond

A WATER BASED SINGLE COMPONENT PAVER PROTECTOR

SURFACE PREPARATION

- ✓ **READ SDS BEFORE HANDLING & APPLICATION**
- ✓ Highly recommended to test a small inconspicuous area first.
- ✓ Always protect neighboring surfaces including wood, carpet, metal, landscaping and other non-masonry surfaces.
- ✓ Caution: Surface is slippery when wet.
- ✓ Before you start, be sure to wear rubber gloves & safety glasses

APPLICATION

Before applying, mix well with a mixing paint paddle. Apply with a pump sprayer fan tip and low pressure. Apply one good application into the sand joint about 6"-9" from the surface. Sand joint will appear white but dries clear. Work Paver Bond into the sand joint and do not allow sand joint to puddle. Back roll if necessary. Failure to back roll excess may result in blotching or turning white and will waste the product. On driveways, allow paver bond to dry for 5-6 days before parking a vehicle.

LIMITATIONS

Classic Paver Bond is harmful to vinyl tile, linoleum, asphalt, plastics, rubber and synthetics. This product will remove old adhesive residue from tile, carpet and wood flooring. Classic Coatings Systems liability, either expressed or implied is limited solely to the replacement of this product, when proven to be defective and does not include any labor cost or consequential damages.

MATERIAL HANDLING

Refer to our website for our Safety Data Sheets. Please review Classic Coatings Technical application specification for full installation procedures, however prior to use or handling material, thoroughly read all safety precautions and safety data sheets (SDS). www.ClassicCoatingsSystems.com

CAUTION

Keep away from children. Do not take internally. Contact may cause eye or skin irritation. Always use safety gloves, appropriate eye protection and appropriate OSHA/ NOSH approved respirator in areas with poor ventilation, and when exposed to spray mist, both outdoors and indoors. Refer to SDS for handling instructions. **FIRST AID:** If ingested, seek medical attention immediately, in case of eye contact, wash thoroughly with soap and water, if irritation occurs, seek medical attention.

KEEP OUT OF REACH OF CHILDREN & PETS

DISCLAIMER

Classic Coatings believes this information to be true to the best of our knowledge and products are of the highest quality and uniform within manufacturing tolerances. Since no control is exercised over product use, no warranty, expressed or implied is made to the effect of such use and no liability is assumed directly or indirectly from their use. Buyers and users are encouraged to conduct their own test prior to application.

HANDLING PRECAUTIONS:

Use only with adequate ventilation. An appropriate cartridge type respirator must be used during application in confined areas. Avoid contact with skin. Protective gloves, eyewear and clothing are recommended.

PROP 65 WARNING:

Classic Coatings, as a blender of processed material in the State of California, is required by Proposition 65 to warn that one or more of the components contained in the product contain chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. The State of California (Proposition 65) requires this warning in the absence of definitive testing to prove that the defined risks do not exist. We believe this product complies with all other applicable state and federal laws and regulations governing manufacturing, distribution and intended use. User is solely responsible for the legal disposal of this container and/or its contents.

WARRANTY:

Classic Coating products are warranted for one year after date of purchase. Please refer to the Limited Material warranty for additional clarification. **NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY.** We warrant that our products are manufactured to strict quality assurance specifications and that the information supplied by us is accurate to the best of our knowledge. Such information supplied about our products is not a representation or a warranty. It is supplied on the condition that you shall make your own tests to determine the suitability of our product for your particular purpose. Any use or application other than recommended herein is the sole responsibility of the user. Listed physical properties are typical and should not be construed as specifications. **NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, REGARDING SUCH OTHER INFORMATION, THE DATA ON WHICH IT IS BASED, OR THE RESULTS YOU WILL OBTAIN FROM ITS USE. NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, THAT OUR PRODUCT SHALL BE MERCHANTABLE OR THAT OUR PRODUCT SHALL BE FIT FOR ANY PARTICULAR PURPOSE. NO WARRANTY IS MADE**

THAT THE USE OF SUCH INFORMATION OR OUR PRODUCT WILL NOT INFRINGE UPON ANY PATENT. We shall have no liability for incidental or consequential damages, direct or indirect. Our liability is limited to the net selling price of our product or the replacement of our product, at our option. Acceptance of delivery of our product means that you have accepted the terms of this warranty whether or not purchase orders or other documents state terms that vary from this warranty. No representative is authorized to make any representation or warranty or assume any other liability on our behalf with any sale of our products. Our products contain chemicals that may CAUSE SERIOUS PHYSICAL INJURY. BEFORE USING, READ THE MATERIAL SAFETY DATA SHEET & FOLLOW ALL PRECAUTIONS TO PREVENT BODILY HARM.

Technical assistance and info. is available by calling: (951) 279-2600
www.ClassicCoatingsSystems.com