



Classic Color Chips

Paint Chips For 100% Solid Epoxy, Water Base Epoxy and Sealers



COVERAGE:

Coverage will vary depending on use and thickness of your epoxy.

PACKAGING:

- 2 lbs (0.91 kg)
- 55 lbs (24.95 kg)

STORAGE:

Keep in a cool, dry location out of direct sunlight.

Store at a temperature between 40°F (4°C) and 90°F (32°C).

SHELF LIFE:

8 years

COLOR:

12 Color Blends; Can be combined for custom blends

DESCRIPTION

Classic Color Chips are a durable and seamless flooring system that is chemical resistant as long as a Classic CRU Sealer is used. Our chips are used for a variety of decorative applications and provide a beautiful color and unique texture to match any design theme or surroundings. These acrylic paint chips are 1/4 inch in size and are available in 12 different blends. They can also be combined for a customized look.

Available Colors:

Nautical, Storm Cloud, Oatmeal, Evergreen, Asphalt, Boulder Gray, Raisin Bran, Salt & Pepper, Chili Blend, Oyster Shell, Latte and Mountain Blend.

New concrete must cure for 28 days before applying.

ADVANTAGES

Many color options for decorative finishes
Long Lasting
For Interior and Exterior Use
Seamless
Easy Application
Easy Clean Up
Chemical Resistant

LIMITATIONS

Chips must be sealed
Application temperatures must be between 50° F and 90° F
Designed for professional use only
Chips are random in shape
Do not allow water on wet epoxy or unsealed color chips
Always do a sample before applying all over

TYPICAL USAGE

- Interior & Exterior
- Showrooms
- Restaurants
- Garages
- Recreation Rooms
- Bathrooms
- Kitchens

Visit us online:
ClassicCoatingSystems.com

See Our Website Gallery
to Get Inspired and
View How-to Videos & SDS

REVISED: August 2018

Classic Coating Systems • 255 Citation, Corona, CA 92880

© 2015 Classic Coatings Systems Inc. All rights reserved.



Classic Color Chips

Paint Chips For 100% Solid Epoxy, Water Base Epoxy and Sealers

SURFACE PREPARATION

- ✓ **READ SDS BEFORE HANDLING & APPLICATION**
- ✓ Highly recommended to test a small inconspicuous area first.
- ✓ Always protect neighboring surfaces including wood, carpet, metal, landscaping and other non-masonry surfaces.
- ✓ Clean concrete with Classic Super Eco-Etch before staining.
- ✓ Before you start staining wear rubber gloves & safety glasses
- ✓ New concrete must cure for 28 days before stain is applied.

Always clean your surfaces to remove oil, dirt, debris or any other foreign matter before applying. Stain your surface with a like color to avoid seeing the blank surface through any spots the paint chips may miss during the application process. Apply a coat of epoxy before distributing the color chips onto the surface. We recommend using our 100% Epoxy (CE500) or our Water Base Epoxy (EW2) • Epoxy is clear but color packs to match your chips are available and are highly recommended.

HOW TO MIX

When using more than one package of chips, mix them together prior to applying in order to achieve a consistent blend.

APPLICATION

Coverage will vary depending on use and thickness of your epoxy. When using more than one package of chips, mix them together prior to applying in order to achieve a consistent blend. Lightly distribute color chips over the wet epoxy on your surface. Once epoxy is dry, sweep loose color chips off and remove from your surface. Scrape the floor with a drywall scraper to remove any leftover chips. Only seal the surface with a Classic Coatings Sealer.

HANDLING PRECAUTIONS:

Use only with adequate ventilation. An appropriate cartridge type respirator must be used during application in confined areas. Avoid contact with skin. Protective gloves, eyewear and clothing are recommended.

PROP 65 WARNING:

Classic Coatings, as a blender of processed material in the State of California, is required by Proposition 65 to warn that one or more of the components contained in the product contain chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. The State of California (Proposition 65) requires this warning in the absence of definitive testing to prove that the defined risks do not exist. We believe this product complies with all other applicable state and federal laws and regulations governing manufacturing, distribution and intended use. User is solely responsible for the legal disposal of this container and/or its contents.

WARRANTY:

Classic Coating products are warranted for one year after date of purchase. Please refer to the Limited Material warranty for additional clarification. NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY. We warrant that our products are manufactured to strict quality assurance specifications and that the information supplied by us is accurate to the best of our knowledge. Such information supplied about our products is not a representation or a warranty. It is supplied on the condition that you shall make your own tests to determine the suitability of our product for your particular purpose. Any use or application other than recommended herein is the sole responsibility of the user. Listed physical properties are typical and should not be construed as specifications. NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, REGARDING SUCH OTHER INFORMATION, THE DATA ON WHICH IT IS BASED, OR THE RESULTS YOU WILL OBTAIN FROM ITS USE. NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, THAT OUR PRODUCT SHALL BE MERCHANTABILITY OR THAT OUR PRODUCT SHALL BE FIT FOR ANY PARTICULAR PURPOSE. NO WARRANTY IS MADE

THAT THE USE OF SUCH INFORMATION OR OUR PRODUCT WILL NOT INFRINGE UPON ANY PATENT. We shall have no liability for incidental or consequential damages, direct or indirect. Our liability is limited to the net selling price of our product or the replacement of our product, at our option. Acceptance of delivery of our product means that you have accepted the terms of this warranty whether or not purchase orders or other documents state terms that vary from this warranty. No representative is authorized to make any representation or warranty or assume any other liability on our behalf with any sale of our products. Our products contain chemicals that may CAUSE SERIOUS PHYSICAL INJURY. BEFORE USING, READ THE MATERIAL SAFETY DATA SHEET & FOLLOW ALL PRECAUTIONS TO PREVENT BODILY HARM.

Technical assistance and info. is available by calling: (714) 720-6954
www.ClassicCoatingsSystems.com