



# Gator Grip

## TDS

**DESCRIPTION AND BASIC USE** • Gator Grip is a finely ground polymer material that is added to concrete sealers to provide slip resistance and fine texturing. It can be added into most film-forming water based and solvent-based sealers. Gator Grip provides improved chemical and abrasion resistance. It is more comfortable to bare feet on treated surfaces than sand or aggregate additives. The product's low density and insolubility characteristics will help reduce settling and provide optimum performance in its various applications, all without changing the viscosity. When a slip-resistant surface is desired, Gator Grip puts "bite" on concrete surfaces and is ideal around properly prepared areas where water or moisture can accumulate. This includes walkways, driveways, garage floors, patios, pool decks, and other surfaces.

**LIMITATIONS** • Gator Grip will increase the texturing effect of a sealer, but the addition of the slip-resistant additive should not be considered non-skid, anti-skid or non-slip.

**COVERAGE** • Gator Grip is designed to be incorporated into a suitable concrete sealer. Minimum addition ratios are 2.4 oz. per gallon and 12 oz. per 5 gallons. Additional Gator Grip can be added, depending on the desired texturing effect. Do not exceed 3 oz. per gallon.

**PREPARATION** • Follow surface preparation directions of sealer being applied.

**APPLICATION** • Stir, while slowly adding Gator Grip to the container of sealer. The product may float at first, but once it has wet out, it will mix in easily. In thinner products, occasional stirring during application may be required to keep the particles well suspended within the coating. It is recommended that when mixing Gator Grip into unfamiliar sealers, that a small test batch is mixed, followed by a small test application. Apply your first layer of sealer with a sprayer without Gator Grip added. For the second layer, mix Gator Grip into sealer for 5 to 10 minutes then apply with a roller. Do not re-roll wet areas. \*Though a sprayer can be used, be aware that some low-pressure pump-up sprayers may not be able to dispense sealers with Gator Grip.

**MAINTENANCE** • Over time, Gator Grip may wear down, particularly in areas with high traffic. It is advisable to reapply a mixture of a Classic Sealer and Gator Grip to areas where Gator Grip has worn down.

**WARNING** • KEEP OUT OF REACH OF CHILDREN. Gator Grip is not hazardous and does not contain silica, but should be treated as a nuisance dust while incorporating it into its intended vehicle. Use with adequate ventilation. Use appropriate, properly fitted respirator protection filter apparatus and avoid breathing dust and particles. If dizziness, headache or eye watering occurs, get to fresh air; leave area immediately. In case of eye contact, flush with large amounts of water for at least 15 minutes. Seek medical attention if irritation persists. Do not take internally. If swallowed, seek medical attention immediately. Keep out of reach of children. Close container after each use. Use protective clothing to avoid contact with skin and eyes. Refer to Material Safety Data Sheet for complete health and safety information. USE ONLY WITH ADEQUATE VENTILATION.

**WARRANTY** • These products are warranted to be of uniform quality with manufacturing tolerances. Since no control is exercised over their use, no warranty, express or implied, is made as to the effect of such use. Sellers & manufacturers obligation under this warranty shall be limited to refunding the purchase price of that portion of the material proven to be defective.